

**Declaration of performance: No. 0029-CPR-2020/11/04**

- 1) Unique identification code of the product-type *AMPHIBIA 3000 GRIP*
- 2) Use and intended uses for the construction product, in compliance with the relative harmonised technical specification, as established by the manufacturer *T-type multilayer plastic membranes designed to prevent rising damp from the ground and for the waterproofing of underground structures in accordance with the harmonised standard UNI EN 13967:2012*
- 3) Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5) *VOLTECO S.p.A. - Via delle Industrie, 47 - Ponzano Veneto (Italy) www.volteco.com*
- 4) System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in annex V *System 2+ / System 4 for reaction to fire*
- 5) In case of the declaration of performance concerning a construction product covered by a harmonised standard *Notified body **Bureau Veritas** identification n° 1370 performed the initial inspection of the manufacturing plant and of factory production control (FPC) and the continuous surveillance, assessment and evaluation of FPC and issued the certificate of conformity of the FPC n° 1294. In case of the declaration of performance (DOP) concerning a construction product covered by the harmonized standards: EN 13967:2012 - Including annexes*

## 6) Declared performance:

| Performance specifications   | Performance                           |
|--|---------------------------------------|
| Reaction to fire   | Class E                               |
| Water tightness  | Test passed (24 h/700 kPa)            |
| Tearing strength (longitudinal)                                    | > 450 N                               |
| Tearing strength (transverse)                                      | > 450 N                               |
| Impact resistance  | Method A: 300 mm<br>Method B: 1750 mm |
| Tensile strength (longitudinal)                                    | > 300 N/50mm                          |
| Tensile strength (transverse)                                      | > 250 N/50mm                          |
| Resistance to static load  | 20 kg                                 |
| Durability - Water tightness after exposure to chemical substances | Test passed                           |
| Durability - Water tightness after artificial ageing               | Test passed                           |
| Joint strength   | 472 N                                 |

- 7) The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

**VOLTECO S.p.A.**

Via delle Industrie, 47 - 31050 Ponzano Veneto (TV) Italy

Tel. +3904229663 - Fax +390422966401

volteco@volteco.it - www.volteco.it

Signed for and on behalf of the manufacturer by Marco Ruzzier Laboratory Manager

-----  
(name and function)



Ponzano Veneto, 2020/11/04 -----

Rev. 2.0 2020/11/04

