



**Number: UK9-56**

**DECLARATION OF PERFORMANCE**

In accordance with Annex III of Registration (EU) No. 305/2011

(Construction Product Regulation)

For the product Proofex Engage

1. Unique identification code of the product-type:  
**EN 13967 Flexible sheets for waterproofing**
2. Type, batch or serial number or other identifying mark to identify the construction product as set out in Article 11 (4):  
**Batch Number: See product packaging**
3. Intended use as foreseen by the manufacturer of the construction product in accordance with the harmonised technical specification:  
**EN13967: Flexible sheet for waterproofing (Class Type A and Type T)**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as set out in article 11 (5)



**Fosroc Limited**  
**Drayton Manor Business Park**  
**Coleshill Road, Tamworth**  
**Staffordshire, B78 3 TL, UK**

5. Name and contact address of the authorised representative who has received a mandate for the tasks set out on Article 12 (2):  
**Not Relevant**
6. System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V  
**System 2+**
7. In the case of a declaration of performance concerning a construction product that is covered by a harmonised standard  

The notified body, BBA, identification number 0836, has carried out initial inspection of the factory and factory production control as well as continuous surveillance, assessment and evaluation of factory production control according to system 2+ and issued the following:  
**Certificate of Factory Production Control**  
**No. 0836-FPC-09/FO13**
8. In case of a declaration of performance concerning a construction product for which a European Technical Assessment was issued  
**Not Relevant**
9. Declared performance

Essential Characteristics	Performance	Harmonised technical specification
<b>Watertightness</b>	No evidence of penetration at 6m head	EN 1928
<b>Resistance to impact</b>	1500 mm	EN 12691
<b>Dangerous substances</b>	Conforms with 5.17	
<b>Resistance to static load</b>	15 kg	EN 12730



## Number: UK9-56

<b>Elongation at break</b>	Long. >300% Trans. >200%	EN 12311-1
<b>Tensile Properties</b>	Long. >10.0 N/mm <sup>2</sup> Trans. >8.0 N/mm <sup>2</sup>	EN 12311-1
<b>Water vapour resistance after artificial ageing</b>	Pass	EN 1296/EN 1931
<b>Resistance to tearing</b>	720 N (longitudinal)	EN 12310-1
<b>Shear resistance of joints</b>	>= 220 N (lap) >= 150 N (butt)	EN12317-1
<b>Water vapour properties</b>	Sd= 400 m	EN 1931
<b>Length</b>	30 m	EN1848-1
<b>Width</b>	1.27 m	EN1848-1
<b>Thickness</b>	4 -5 mm	EN 1849-1

When specified technical documentation in accordance with Articles 37 or 38 was used, the requirements that the product fulfils:

### Not applicable

The performance of the product set out in numbers 1 and 2 corresponds to the declared performance set out in number 9. The manufacturer as defined in number 4 is solely responsible for drawing up this declaration of performance.

Signed for the manufacturer and in the name of the manufacturer by:

A handwritten signature in black ink that reads "Jeremy Bell".

Jeremy Bell,  
Technical Quality Manager

Place and Date of Issue:      28/06/2013      Tamworth